



3 POLES

EN 60947-3 CHARACTERISTICS

		SQ025	SQ032
Rated operating voltage Ue	V	690	690
Rated insulation voltage Ui	V	690	690
Rated impulse withstand voltage Uimp (sectionable)	kV	8	8
Rated thermal current Ith	A	32	40
Rated thermal current in enclosed Ithe	A	32	40
Frequency	Hz	50/60	50/60

RATED OPERATING CURRENT le: alternate current

AC-21A Switching resistive loads with light overloads	690V	A	32	40
AC-22A Switching mixed resistive and inductive loads at light overloads	500V	A	-	-
	690V	A	25	32
AC-23A Periodic switching of motors	3 phase - 3 poles	230V	A/kW	25/7,5
		400V	A/kW	25/15
		500V	A/kW	25/15
		690V	A/kW	16/15
AC3 Starting of cage motors (interruption while running)	3 phase - 3 poles	230V	A/kW	22/5,5
		400V	A/kW	22/11
		500V	A/kW	22/11
		690V	A/kW	16/11
Nominal interruption power AC-23A (cosfi 0,45)	230V	A	200	256
	400V	A	200	256
	500V	A	200	256
	690V	A	128	160

SHORT CIRCUIT CHARACTERISTICS

Rated short-time short circuit withstand current Icw (1s)	A	800	800
Rated short circuit making capacity Icm	A	1500	1500
Conditional rated short circuit withstand current	kA	10	10
Fuse rating gG	500V	A	-
	690V	A	40

UL 508 CHARACTERISTICS

General use	600V ac	A	32	40
Standard motors load	120V ac	HP(FLA)	1,5 (20)	2 (24)
	200÷208V ac	HP	2	3
	240V ac	HP(FLA)	3 (17)	5 (28)
	200÷208V ac	HP	7,5	10
	240V ac	HP(FLA)	7,5 (22)	10 (28)
	480V ac	HP(FLA)	10 (14)	15 (21)
	600V ac	HP(FLA)	15 (17)	20 (22)